

U Series Thermal Transfer Overprinter

All in one printer

32mm,53mm print head,intermittent and continuous combined



Patented dual motor ribbon drive technology

Consistent ribbon print gap, optimized ribbon usage

Consistent ribbon tension throughout the entire roll

Easy ribbon loading

Powerful software

UI comes with create and edit function

Option to use PC as an UI

Customizable print function

Modular design

Simple structure, stable performance

Ease in maintenance, minimal servicing

Suits both 32mm and 53mm print head

Technical References

Model	U32	U53
Print Area	Int.:32x80mm;Con.:32x180mm	Int.:53x80mm;Con.:53x180mm
Print Head	32mm 300DPI	53mm 300DPI
Print Speed	Int.:100mm/s~400mm/s;Con.:Max.800mm/s	
Print Frequency	Max.400 times/minute	
Ribbon Size	33mmx600m	55mmx600m
	*Max 900m,more sizes and colors available	
Print Gap	0.5mm and adjustable	
Software Interface	RS232 industrial port/USB transfer/Network Interface	
Hardware Interface	Input:print trigger,encoder	
	Output:Print/Warning/Fault	
User Interface	Warning and Error indication Job file creation/Self Diagnostic Industrial PC/Color touch screen with USB ports	
Print Body Features	Multiple Language Input	
	Real date and time/Best before date/Expiry date Image rotation/Font Selection/Logo/Serial numbering Customized Code/Random 2D code/Barcode/Shift code	
Weight	Appr. 6.0KG	
Size	L200mm x H180mm x W160mm	
Power/Air Supply	90~240 VAC	
	Max 6 bar compressed air	
Operating Environment	Temperature:0~40 °C Humidity:0~90%	

*Only the length of customized ribbon reaches to Max. 900 M

上海研捷机电设备有限公司
Shanghai Yanjie Technology Co.,Ltd
Shanghai Contact:
Tel:+86-21-62829208
Fax:+86-21-62829209
Email:marketing@yanjietech.com

Overseas Contact:
Tel:+65-82007786
Email:dickson.chan@yanjietech.com



<http://www.yanjietech.com>